

NEW 2008 Hydraulic Panel Pumps

MODEL T5HS PANEL PUMP

The same rugged, reliable construction you have come to depend upon with the T5 Panel Pump (page 4), with numerous upgrades.



Features

- ◆ New, attractive design
- ◆ Double-acting, high efficiency
- ◆ 12% faster than T5 @ 5.6 ml/stroke
- ◆ 60% faster than most popular competing systems
- ◆ Gauge – large, 2" diameter, easy to read, flush mount; all stainless steel case
- ◆ 5000 psi maximum pressure
- ◆ Self purging of air, self priming
- ◆ Easy to install

Construction

- ◆ Aircraft-quality aluminum
- ◆ Filtered intake from reservoir
- ◆ Adjustable relief valve
- ◆ Flush gauges, 2" diameter Type 316 stainless steel case
- ◆ Valves – zero leakage to 6000 psi

All panels come complete with handle, hardware, reservoir, and reservoir hose

DESCRIPTION	PANEL DIMENSIONS		DEPTH		WEIGHT		PART No.
	INCH	MM	IN	MM	LB	KG	
1 Function	7.0 x 8.63	178 x 219	4.6	117	6.1	2.7	T5HS-1
2 Function	8.8 x 10.0	222 x 254	4.6	117	7.0	3.1	T5HS-2
3,4 Function	8.8 x 10.0	222 x 254	4.6	117	7.5	3.4	T5HS-4

Data subject to change.

This new style T5HS Panel Pump adds style, speed, and greater functionality to the already powerful T5 Panel (page 4). Careful sculpting of internal parts and passages has enabled us to increase the speeds and efficiency of the pump, change the location of the gauge and handle, and improve the face design.

Measure the difference for yourself.

Cylinder Rams	To Retract 10" (254mm)	
	Pump Strokes Needed	Seconds Needed <small>(When pumping two strokes per second)</small>
-10	27	14
-12	39	20
-17	58	29
-22	75	38

For more information call: 920-233-4242 or email: info@sailtec.com

